

Seal 80 Pro D

Product information

The SEAL 80 Pro D is a 2 metre wide moulder, laminator and encapsulator ideal for the more experienced finisher requiring a highly versatile laminator. Capable of running a wide range of media, this laminator can generate high process speeds. The SEAL 80 Pro D features some new design elements such as: a control panel on a swinging arm, a new feed table, a flip down image guide and outfeed slitters.

Features

- Ergonomic touch pad control panel on a swinging arm enabling operation from the front or rear of the machine
- Output slitters to trim image to size during operation
- Trough to the front of feed table for small rolls of images
- High release silicone rollers for easy cleaning
- Drop-in supply shafts with autogrip for easy loading of materials
- Incorporates easy in-feed table for easy and efficient media handling and set-up
- Simple film tension adjustment
- Automatic upper take-up shaft for removing release liners
- Roll-to-roll capability
- Adjustable settings for increased capacity and oversaturation
- Easy Feed table with built-in tensioning rollers and a flip down image guide for smooth and optimum infeed of media
- Flip-up pull rollers for flatter results when encapsulating and for uninterrupted access when not encapsulating
- Manual nip-adjustment for precision
- 38 mm nip opening for processing a wide range of substrates
- Variable roller technology for better processing

Please also note the Technical data Sheets and Application Note to this product.

For orders, sample requests, questions or suggestions please contact:

Neschen AG | Hans-Neschen-Str. 1 | D-31675 Bückeberg

Phone: +49 (0) 57 22-20 70 | Fax: +49 (0) 57 22-20 71 59 | E-Mail: info@neschen.de | www.neschen.com

of soft substrates

- 2,5n/mm line pressure for superior cold lamination
- Three combi-supply shafts for max. flexibility
- Automatic cooling fans for long runs and extended operations
- Foot switch for hands free operation
- Panick strip for operator safety
- Comprehensive safety system with selfchecking safety eyes and emergency stops
- CE certified



Specifications	
Rollers	Dual heated
Maximum working width	2030 mm
Maximum speed	6 m/min
Electrical requirements	3N/PE 230VAC +/-10% 50/60 Hz, 25 A
Volume production	High

	Hot	Cold
Mounting	yes	yes
Laminating	yes	yes
Encapsulating	yes	yes

Please also note the Technical data Sheets and Application Note to this product.

For orders, sample requests, questions or suggestions please contact:

Neschen AG | Hans-Neschen-Str. 1 | D-31675 Bückeberg

Phone: +49 (0) 57 22-20 70 | Fax: +49 (0) 57 22-20 71 59 | E-Mail: info@neschen.de | www.neschen.com

Details

Sizes :

64240	Seal 80 Pro D	
-------	---------------	--

Please also note the Technical data Sheets and Application Note to this product.

For orders, sample requests, questions or suggestions please contact:

Neschen AG | Hans-Neschen-Str. 1 | D-31675 Bückeberg

Phone: +49 (0) 57 22-20 70 | Fax: +49 (0) 57 22-20 71 59 | E-Mail: info@neschen.de | www.neschen.com